

UTAMA KARYA TECHINDO

Specialist in **Rubber**

UK-SOLID RUBBER PAD

Product Code : UK124 SA0125

UK-Solid Rubber Pad

Solid Rubber Pad are a heavy duty material that provides good resistance as well as Excellent physical properties for use in , machine mounting and wear pads. Rubber materials also display excellent rates of adhesion to a wide variety of fabrics and metals. This combination of properties create an incredibly versatile and dependable material. We supply our Solid Rubber Pad with a thickness of 15mm, 20mm, 30mm, or 40mm in 2m x 1m slabs as standard.



What are UK-Solid Rubber Pad?

Solid Rubber Pad is an economy-grade material, black in colour which has a higher wear resistance and remains flexible even at low temperatures. Natural Rubber (NR) compounds are often mixed with another polymer such as SBR which are intended to improve or add additional properties. UK-Solid rubber pads, is available in a range of hardnesses of 60, 65 and 70 shore A.

KEY FEATURES

- Heavy Duty Product
- Excellent physical properties
- Good weathering & Ozone resistance
- Versatile material
- Resists rotting, abrasion, & cracking

AREA OF APPLICATION

- Heavy machinery mounting pads
- Construction industries
- Padding, skirting & cushioning
- Durable wear strips

TECHNICAL INFORMATION

Polymer	NR/IR/SBR	ASTM D 3677 - 10(2015)
Hardness, Shore A	65 ± 5	ASTM D 2240-15
Tensile strength (Isotropic), Mpa	19.9	ASTM D 412-16
Elongation at break, %	540	ASTM D 412-16
Abrasion resistance, DIN, mm^3	98.4	ASTM D.5963-04(ra2015)